



Jimmy Jib Cranes system

	JimmyJib Standard	JimmyJib Standard +	JimmyJib Giant	JimmyJib Giant +	JimmyJib Super	JimmyJib 21 Feet	JimmyJib Super +	JimmyJib Extreme	JimmyJib 40 Feet
Charge utile maximum (Camera)	27 kg (59.5 lbs)	23 kg (50.7 lbs)	23 kg (50.7 lbs)	23 kg (50.7 lbs)	23 kg (50.7 lbs)	23 kg (50.7 lbs)	23 kg (50.7 lbs)	23 kg (50.7 lbs)	13 kg (28.6 lbs)
<u>Longueur avant</u> (Tête caméra vers Pivot)	<u>1,83 m</u> (6 ft)	<u>2,70 m</u> (8,9 ft)	<u>3,66 m</u> (12 ft)	<u>4,50 m</u> (14.7 ft)	<u>5,50 m</u> (18 ft)	<u>6,40 m</u> (21 ft)	<u>7,32 m</u> (24 ft)	<u>9,14 m</u> (30 ft)	<u>12,20 m</u> (40 ft)
= nombre d'extensions <u>avant</u>	Flèche Cam + [0]	Flèche Cam + [1]	Flèche Cam + [2]	Flèche Cam + [3]	Flèche Cam + [4]	Flèche Cam + [5]	[F.C]+[1]+[sp]+[4]	[F.C]+[3]+[sp]+[4]	Spécial
<u>Longueur arrière</u> (Pivot vers contrepoids)	1,30 m (4.3 ft)	1,30 m (4.3 ft)	1,30 m (4.3 ft)	2,00 m (6.6 ft)	2,00 m (6.6 ft)	2,00 m (6.6 ft)	2,00 m (6.6 ft)	2,80 m (9,2 ft)	2,80 m (9,2 ft)
= nombre d'extensions <u>arrière</u>	[0] + Arrière	[0] + Arrière	[0] + Arrière	[1] + Arrière	[1] + Arrière	[1] + Arrière	[1] + Arrière	[2] + Arrière	[2] + Arrière
= Masse <u>contrepoids</u> arrière	20kg environ	3 x 20kg env.	4 x 20kg env.	5 x 20kg env.	6 x 20kg env.	7 x 20kg env.	8 x 20kg env.	10 x 20kg env.	12 x 20kg env.
Hauteur optique max --> Overslung	5,00 m (16,4 ft)	5,80 m (19 ft)	6,70 m (21,2 ft)	8,00 m (26.2 ft)	8,60 m (28.2 ft)	9,20 m (30.2 ft)	10,00 m (32.8 ft)	11,80 m (38.7 ft)	14,00 m (45.9 ft)
Hauteur optique max --> Underslung	4,00 m (13.1 ft)	4,80 m (15.7 ft)	5,70 m (18.7 ft)	7,00 m (23.0 ft)	7,60 m (24.9 ft)	8,20 m (26.9 ft)	9,10 m (29.9 ft)	10,80 m (35.4 ft)	13,00 m (42.6 ft)
Poids total maximum (sur trépied)	200 kg (441 lbs)	250 kg (550 lbs)	300 kg (660 lbs)	350 kg (770 lbs)	400 kg (880 lbs)	425 kg (935 lbs)	450 kg (990 lbs)	600 kg (1320 lbs)	700 kg (1540 lbs)
Type de dolly recommandé	3-4 WD (J.J.), Tripod (J.J.), Hotdog dolly	3-4 WD (J.J.), Tripod (J.J.), Hotdog dolly	3-4 WD (J.J.), Tripod (J.J.), Hotdog dolly	3-4 WD (J.J.), Tripod (J.J.), Hotdog dolly	3-4 WD (J.J.), Tripod (J.J.), Hotdog dolly	4 WD (J.J.), Tripod (J.J.), Hotdog dolly	4 WD (J.J.), Tripod (J.J.), Hotdog dolly	4 WD (J.J.)	4 WD (J.J.)
Surface de travail pour 360° - Longueur	3,50 m (11.5 ft)	3,50 m (11.5 ft)	3,50 m (11.5 ft)	4,50 m (14.8 ft)	4,50 m (14.8 ft)	4,50 m (14.8 ft)	4,50 m (14.8 ft)	6,00 m (19.7 ft)	6,00 m (19.7 ft)
Surface de travail pour 360° - Largeur	3,50 m (11.5 ft)	3,50 m (11.5 ft)	3,50 m (11.5 ft)	4,50 m (14.8 ft)	4,50 m (14.8 ft)	4,50 m (14.8 ft)	4,50 m (14.8 ft)	6,00 m (19.7 ft)	6,00 m (19.7 ft)
Surface de travail pour 180° - Longueur	3,50 m (11.5 ft)	3,50 m (11.5 ft)	3,50 m (11.5 ft)	4,50 m (14.8 ft)	4,50 m (14.8 ft)	4,50 m (14.8 ft)	4,50 m (14.8 ft)	6,00 m (19.7 ft)	6,00 m (19.7 ft)
Surface de travail pour 180° - Largeur	2,00 m (6.6 ft)	2,00 m (6.6 ft)	2,00 m (6.6 ft)	3,00 m (9.8 ft)	3,00 m (9.8 ft)	3,00 m (9.8 ft)	3,00 m (9.8 ft)	4,50 m (14.8 ft)	4,50 m (14.8 ft)